

DT-V100CG/E, DT-V100CG/U

STANDARD CIRCUIT DIAGRAM

■ NOTE ON USING CIRCUIT DIAGRAMS

1.SAFETY

The components identified by the \triangle symbol and shading are critical for safety. For continued safety replace safety critical components only with manufactures recommended parts.

2.SPECIFIED VOLTAGE AND WAVEFORM VALUES

The voltage and waveform values have been measured under the following conditions.

- (1)Input signal : Colour bar signal
- (2)Setting positions of each knob/button and variable resistor : Original setting position when shipped
- (3)Internal resistance of tester : DC 20k Ω /V
- (4)Oscilloscope sweeping time : H \Rightarrow 20 μ s / div
: V \Rightarrow 5ms / div
: Others \Rightarrow Sweeping time is specified
- (5)Voltage values : All DC voltage values

* Since the voltage values of signal circuit vary to some extent according to adjustments, use them as reference values.

3.INDICATION OF PARTS SYMBOL [EXAMPLE]

- In the PW board : R1209 \rightarrow R209

4.INDICATIONS ON THE CIRCUIT DIAGRAM

(1)Resistors

● Resistance value

- No unit : [Ω]
- K : [k Ω]
- M : [M Ω]

● Rated allowable power

- No indication : 1/16 [W]
- Others : As specified

● Type

- No indication : Carbon resistor
- OMR : Oxide metal film resistor
- MFR : Metal film resistor
- MPR : Metal plate resistor
- UNFR : Uninflamable resistor
- FR : Fusible resistor

* Composition resistor 1/2 [W] is specified as 1/2S or Comp.

(2)Capacitors

● Capacitance value

- 1 or higher : [pF]
- less than 1 : [μ F]

● Withstand voltage

- No indication : DC50[V]
- Others : DC withstand voltage [V]
- AC indicated : AC withstand voltage [V]

* Electrolytic Capacitors

47/50[Example]: Capacitance value [μ F]/withstand voltage[V]

●Type

- No indication : Ceramic capacitor
- MM : Metalized mylar capacitor
- PP : Polypropylene capacitor
- MPP : Metalized polypropylene capacitor
- MF : Metalized film capacitor
- TF : Thin film capacitor
- BP : Bipolar electrolytic capacitor
- TAN : Tantalum capacitor

(3)Coils

- No unit : [μ H]
- Others : As specified

(4)Power Supply




-  : B1  : B2 (12V)
-  : 9V  : 5V

* Respective voltage values are indicated





(5)Test point

-  : Test point
-  : Only test point display



(6)Connecting method

-  : Connector
-  : Wrapping or soldering
-  : Receptacle

(7)Ground symbol

-  : LIVE side ground
-  : ISOLATED(NEUTRAL) side ground
-  : EARTH ground
-  : DIGITAL ground

5.NOTE FOR REPAIRING SERVICE

This model's power circuit is partly different in the GND. The difference of the GND is shown by the LIVE : () side GND and the ISOLATED(NEUTRAL) : () side GND. Therefore, care must be taken for the following points.

- (1)Do not touch the LIVE side GND or the LIVE side GND and the ISOLATED(NEUTRAL) side GND simultaneously. if the above caution is not respected, an electric shock may be caused. Therefore, make sure that the power cord is surely removed from the receptacle when, for example, the chassis is pulled out.
- (2)Do not short between the LIVE side GND and ISOLATED(NEUTRAL) side GND or never measure with a measuring apparatus (oscilloscope, etc.) the LIVE side GND and ISOLATED(NEUTRAL) side GND at the same time. If the above precaution is not respected, a fuse or any parts will be broken.

◆ Since the circuit diagram is a standard one, the circuit and circuit constants may be subject to change for improvement without any notice.

NOTE

◆ Due improvement in performance, some part numbers show in the circuit diagram may not agree with those indicated in the part list.

When ordering parts, please use the numbers that appear in the Parts List.

CONTENTS

SEMICONDUCTOR SHAPES2-2

BLOCK DIAGRAM2-3

CIRCUIT DIAGRAMS2-5

 SIGNAL PWB CIRCUIT DIAGRAM 2-5

 MAIN PWB CIRCUIT DIAGRAM2-11

 CRT SOCKET PWB CIRCUIT DIAGRAM2-13

 FRONT CONTROL PWB CIRCUIT DIAGRAM2-15

 TALLY PWB CIRCUIT DIAGRAM2-17

 LINE FILTER PWB CIRCUIT DIAGRAM2-19

PATTERN DIAGRAMS 2-21

 SIGNAL PWB PATTERN 2-21

 MAIN PWB PATTERN2-25

 CRT SOCKET PWB PATTERN2-27

 LINE FILTER PWB PATTERN2-27

 FRONT CONTROL PWB PATTERN2-28







 TALLY PWB PATTERN2-28

USING P.W. BOARD






PWB ASS'Y name	DT-V100CGEA	DT-V100CGIUA
MAIN P.W. BOARD	FX1189A-H2	←
CRT SOCKET P.W. BOARD	FX3076A-H2	←
FILTER P.W. BOARD	FX9096A-H2	←
FRONT CONTROL P.W. BOARD	FX4093A-H2	←
SIGNAL P.W. BOARD	FX6145A-H2	←
TALLY P.W. BOARD	FX7058A-H2	←

SEMICONDUCTOR SHAPES



TRANSISTOR

BOTTOM VIEW	FRONT VIEW				TOP VIEW
					

IC

BOTTOM VIEW	FRONT VIEW			TOP VIEW
				


CHIP IC


TOP VIEW		
		

(No.YA322)2-3


2-4(No.YA322)

SIGNAL PWB CIRCUIT DIAGRAM (1/3) SHEET1






SIGNAL PWB CIRCUIT DIAGRAM (3/3) SHEET 3




MAIN PWB CIRCUIT DIAGRAM SHEET 4



(No.YA322)2-11


2-12(No.YA322)




(No.YA322)2-13

2-14(No.YA322)

FRONT CONTROL PWB CIRCUIT DIAGRAM SHEET 6




FRONT CONTROL PWB ASS'Y
FX-4093A-H2



TALLY PWB ASS'Y
FX-7058A-H2


LINE FILTER PWB CIRCUIT DIAGRAM SHEET 8




(No.YA322)2-19


2-20(No.YA322)

PATTERN DIAGRAMS
SIGNAL PWB PATTERN [SOLDER SIDE]






MAIN PWB PATTERN




(No.YA322)2-25

2-26(No.YA322)


CRT SOCKET PWB PATTERN




LINE FILTER PWB PATTERN




FRONT CONTROL PWB PATTERN [SOLDER SIDE]



FRONT CONTROL PWB PATTERN [PARTS SIDE]



TALLY PWB PATTERN [SOLDER SIDE]



TALLY PWB PATTERN [PARTS SIDE]

